

CLI Manual

CLI Manual

Table of Contents

Preface	vi
Objective	vi
Target audience	vi
Conventions used in this manual	vi
1. Help	1
Getting Help	1
2. Login	2
To access the CLI	2
To access the Container	2
3. Knowing the CLI commands	3
List of commands	3
Command apply	4
Command astranslation	4
Command bridge	5
Command clear-cfg	5
Command clock	6
Command date2ts	6
Command db-check	7
Command disk-cache	7
Command dns	7
Command dnsquery	8
Command exit	8
Command flowcollect	8
Command flow-probe	8
Command flow-sampling	9
Command hds-query	9
Field list	10
Command hostname	10
Command interface	10
Command logview	11
Command ntp	12
Command ntpquery	12
Command packet-dump	13
Command password	14
Command patchtool	15
Command ping	15
Command poweroff	16
Command probe	16
Command process	17
Command prompt	18
Command restart	18
Command restore	18
Command resum	18
Command route	19
Adding route	19
Removing route	19
Command save	20
Command service	20
Command smart-diag	21
Command show	21
Show all	22

Show arptable	22
Show bridge	22
Show clock	22
Show cpu	23
Show diag	23
Show disk-cache	23
Show dns	24
Show flowcollect	24
Show flow-probe	24
Show flow-sampling	24
Show hostname	24
Show interface	25
Show memory	25
Show ntp	25
Show probe	26
Show process	26
Show prompt	26
Show route	26
Show service	26
Show snmp-cfg	27
Show speed	27
Show storage	27
Show uptime	27
Show version	27
Show webserver	27
Command show-cfg	28
Command show-how	29
Command snmp	29
Command snmp-cfg	30
Command speed	31
Command storage	31
Command traceroute	32
Command ts2date	32
Command update	33
Command version	33
Command webserver	34

List of Tables

1. Manual conventions	vi
1.1. Getting Help	1
3.1. List of commands	3
3.2. Bridge Command Notation	5
3.3. Clock Command Notation	6
3.4. Date2ts Command Notation	6
3.5. Flow-probe Command Notation	9
3.6. Hds-query Command Notation	9
3.7. TRAFip - List of Fields	10
3.8. SLAview - List of Fields	10
3.9. Hostname command	10
3.10. Interface Command	11
3.11. Logview Command	11
3.12. NTP Command Notation	12
3.13. Ntpquery Command Notation	13
3.14. Ntpquery - Left margin notation	13
3.15. Packet-dump Command Notation	14
3.16. Ping Command Notation	15
3.17. Probe Command Notation	17
3.18. Process Command - Output format	17
3.19. Resum Command Notation	19
3.20. Route Command Notation	19
3.21. Services	20
3.22. Show command	21
3.23. Show Clock Notation	22
3.24. Show-cfg command	28
3.25. Show-how command	29
3.26. SNMP Command Notation	30
3.27. SNMPv3 parameters	30
3.28. Speed Command Notation	31
3.29. Storage Command Notation	32
3.30. Traceroute Command Notation	32
3.31. Ts2date Command Notation	33
3.32. Update Command Notation	33

Preface

Objective

This manual describes how to configure and maintain Telcomanager appliance using the CLI (Command Line Interface).

Target audience

This manual was designed for network administrators, network consultants and Telcomanager partners.

Conventions used in this manual

This document uses the following conventions:

Table 1. Manual conventions

Item	Convention
[]	Square brackets enclose an optional element (keyword or argument).
< >	Angle brackets enclose a required element (keyword or argument).
Examples	This font means the text is an example.
#	Comments explaining the command used in the example.
Commands, buttons and keywords	Boldface font.

Chapter 1. Help

Getting Help

This section shows how to get help using the CLI.

Table 1.1. Getting Help

Command	Purpose
<code>?</code>	Lists all commands available.
<code>command ?</code>	Shows overview about the command. Example: <code>ts2date?</code> or <code>ts2date ?</code>
<code>abbreviated-command-entry <Tab></code>	Completes a partial command name. Example: <code>ts2<Tab></code> will be completed and the command ts2date will be shown on CLI

Chapter 2. Login

To access the CLI

First of all, you will need an SSH client to access the Command-line interface (CLI).

You can use PuTTY, the popular free SSH and telnet client for Windows. It can be downloaded using this link <http://www.putty.org>.

Execute the program and make sure the **PuTTY Configuration** window is open. To configure this program, follow the procedure below:

1. Select the **Session** tab.
2. Enter the IP address of your appliance.
3. Select SSH connection type and don't forget to check if the port is 22.
4. Click on **Open** button

To login, follow the next procedure:

1. Enter with **admin** in "login as:".
2. Use the password **telcoadm** (don't forget to change it using the **password** command).

Finally, the string below will be shown on your CLI and you will be logged.

```
TelcoAppliance>
```

To access the Container

To login, follow the next procedure:

1. Using the browser of your preference, access <IP>:8080;
2. Fill the **Username** field with "admin";
3. Fill the **Password** field with "t3lc0m4n!@#";
4. Click on **Login** button.

Chapter 3. Knowing the CLI commands

List of commands

This table provides all the commands you can use and their description.

Table 3.1. List of commands

Command	Description
apply	Apply current settings to running configuration
astranslation	Starts ASN translation
bridge	Bridge configuration
clear-cfg	Clear temporary configuration
clock	Set system clock
date2ts	Convert date format to timestamp
db-check	Checks database integrity
disk-cache	Appliance tuning
dns	DNS configuration
dnsquery	Query Internet name servers interactively
exit	Exit from the CLI
flowcollect	Flow collector configuration
flow-probe	Flow-probe configuration
flow-sampling	Set flow sampling
hds-query	HDS viewer
hostname	Hostname configuration
interface	Interface configuration
logview	Print logs
ntp	NTP configuration
ntpquery	NTP server monitoring tool
packet-dump	Capture packets
password	Update user authentication
patchtool	Patch tool
ping	Send ICMP echo messages
poweroff	Turn off
probe	Probe running system information
process	Kill process
prompt	CLI string configuration
restart	Restart system
restore	Restore system configuration
resum	Re-summarize the interval between two instants

Command	Description
route	Route configuration
save	Save to startup configuration after apply
service	Service management utility
show	Show running system information
show-cfg	Show config system information before apply
show-how	Show how to replicate running system information
smart-diag	Print SMART information
snmp	SNMP statistics
snmp-cfg	Appliance SNMP agent
speed	Interface speed configuration
storage	Data storage management utility
traceroute	Trace route to destination
ts2date	Convert timestamp to date format
update	System update
version	Version information
webserver	Virtual root configuration

Command apply

After a change using another command, you have to apply the current settings. If you want this modification to be definitely saved, do not forget to use the command **save** after.

For instance:

```
TelcoAppliance> show prompt
    Prompt configuration:
      string: TelcoAppliance
TelcoAppliance> prompt Test
TelcoAppliance> apply
    Please, wait.
    Setting up phase0
    Setting up phase1
    Setting up phase2
    Setting up phase3
(Unsaved) Test>
```

Command astranslation

Using this command, it's possible to translate source and destination ASN (Autonomous system number) by source and destination IP, respectively.

It has 4 parameters: **enable**, **disable**, **update** and **status**. Check below.

To enable this feature, use the following command: **astranslation enable <URL>**. A message will be displayed to confirm if you really desire to download the table containing the ASN. To proceed, type **yes**.

To update the file containing the table, type: **astranslation update <URL>**.

To disable the translation, use the command: **astranslation disable**.

To show the current astranslation configuration, use the command: **astranslation status**.

Command bridge

Using this command you can show or drop a bridge or create a new one. Besides it's possible to add or remove an interface to a bridge.

To see the current bridge configuration, use **show bridge**

To create a bridge, use **bridge create <NAME>**

To drop a bridge, use **bridge drop <NAME>**

To add an interface to a bridge, use **bridge <NAME> add <INTERFACE>**.

To remove an interface to a bridge, use **bridge <NAME> remove <INTERFACE>**.

Table 3.2. Bridge Command Notation

Notation	Description
NAME	"brdX", where "X" is the bridge number
INTERFACE	"netX", where "X" is the interface number

Command clear-cfg

You can check a change before to apply using the command **show-cfg**. If you do not want this modification anymore, you can use **clear-cfg** to clear this temporary configuration.

For instance:

```
TelcoAppliance> show ntp #Checking ntp state
NTP configuration:
  server-1: 0.pool.ntp.org
  server-2: 1.pool.ntp.org
  server-3: 0.br.pool.ntp.org
  state: on
```

```
TelcoAppliance> ntp state off #Changing ntp state
```

```
TelcoAppliance> show ntp #ntp state before to apply
NTP configuration:
  server-1: 0.pool.ntp.org
  server-2: 1.pool.ntp.org
  server-3: 0.br.pool.ntp.org
  state: on
```

```
TelcoAppliance> show-cfg ntp #Checking the modification before apply
NTP configuration:
```

```
server-1: 0.pool.ntp.org
server-2: 1.pool.ntp.org
server-3: 0.br.pool.ntp.org
state: off
```

```
TelcoAppliance> clear-cfg #Clear temporary configuration
```

```
TelcoAppliance> show-cfg ntp #Checking if clear-cfg command worked
NTP is not modified.
```

Important

Notice that this command only clear temporary configuration, that is, before to apply.

Command clock

Use this command to configure the system time and date.

To see the current date and time, use **show clock**.

You can change only the date (**clock <DATE>**), only the time (**clock <TIME>**) or the both of them together (**clock <DATE> <TIME>** or **clock <TIME> <DATE>**).

Notation:

Table 3.3. Clock Command Notation

Notation	Description
DATE	"YYYY/mm/dd"; "Y" stands for year, "m" for month, "d" for day
TIME	"HH:MM:SS"; "H" stands for hours, "M" for minutes, "S" for seconds

Important

You will not be able to set clock if NTP is ON.

Command date2ts

If you want to convert date format to timestamp, you have to use the command **date2ts**.

Full command syntax: **date2ts <YEAR> <MONTH> <DAY> <HOUR> <MINUTE>**

Notation:

Table 3.4. Date2ts Command Notation

Notation	Description
YEAR	Full year notation
MONTH	Month, from 1 to 12
DAY	Day, from 1 to 31
HOUR	Hour, from 0 to 23

Notation	Description
MINUTE	Minute, from 0 to 59

Look at the following example:

```
TelcoAppliance> date2ts 2014 07 03 10 30
Timestamp: 1404394200
```

Command db-check

This tool analyses all tables of the system to check database integrity.

To run this command, just to type **db-check** on screen and answering "yes" to the question which asks if you want to proceed.

```
TelcoAppliance> db-check
```

Command disk-cache

Configure the disk-cache parameters using this command.

Available options:

- **disk-cache set dirty_ratio <INTEGER>**. This integer has to be between 10 and 80.
- **disk-cache set dirty_expire <INTEGER>**. This integer has to be between 3000 and 720000.
- **disk-cache set dirty_background_ratio <INTEGER>**. This integer has to be between 10 and 60.
- **disk-cache reset**. This command will reset all parameters to its default value. It has to be followed by apply, save and restart.
- **disk-cache highmem_is_dirtyable <yes|no>**.

Command dns

This command is used to Domain Name System (DNS) configuration.

To display your current DNS configuration, enter **show dns** on screen.

To set primary DNS manually, enter **dns primary <IP>**, which IP is a valid IP address.

To set secondary DNS manually, enter **dns secondary <IP>**, which IP is a valid IP address.

It's possible to specify the IP version. To do this, enter **ipv4** or **ipv6** before enter the IP. For instance:

```
TelcoAppliance> dns primary ipv4 10.0.0.13
TelcoAppliance>
```

When the IP version is not specified, the system consider it as IPv4.

Important

You can't forget to apply and save your modifications.

Command dnsquery

Query Internet name servers interactively using this command.

For instance:

```
TelcoAppliance> dnsquery google.com
Request: google.com
IP:      173.194.119.37
```

```
TelcoAppliance> dnsquery 173.194.119.37
Request: 173.194.119.37
Host:    rio01s08-in-f5.1e100.net
```

Command exit

Use this command to quit from the command-line interface.

Command flowcollect

Define the maximum default number of templates to be kept by the collector. When this limit is reached, the oldest template is discarded.

To do this, enter the command: **flowcollect max_templates <N>**, where **N** is the maximum number of templates.

Important

Use this command very carefully. Only change the maximum default number of templates if it is really necessary.

Command flow-probe

Flow-probe is a process which runs in TRAFip.

To visualize the current flow-probe configuration, enter: **show flow-probe**.

Enable flow-probe typing **flow-probe enable** and disable typing **flow-probe disable**.

You need to configure the destination-ip and the destination-port. So, use the commands: **flow-probe destination-ip <IP>** and **flow-probe destination-port <PORT>**.

To set active flow lifetime, use the command **flow-probe active-timeout [SECONDS]** and, to set inactive flow lifetime, use the command **flow-probe inactive-timeout [SECONDS]**.

You can add an interface to flow-probe, but this interface needs to be added to a bridge. To do this, type the following command: **flow-probe add** <INTERFACE> <MODE>.

Table 3.5. Flow-probe Command Notation

Notation	Description
IP	A valid IP address
PORT	A TCP port number
SECONDS	A positive integer. active-timeout must be between 10 and 3600, and default is 60; inactive-timeout must be between 1 and 60, and default is 15
INTERFACE	"netX", where "X" is the interface number
MODE	Choose the mode: ingress , egress , in-egress or sniffer .

Command flow-sampling

You can set the flow sampling using the command **flow-sampling set** <INTEGER>. This integer value is the minimum number of octets to not discard a flow. It means that the flows with less than <INTEGER> octets will be discarded.

To stop discarding flows, enter the command **flow-sampling unset**.

Command hds-query

To consult the summarized data, you can use this command.

Command syntax: **hds-query select** <SYSTEM> <HDS ID> <FIELD LIST> <START> <END> <PAGED> .

You can also squeeze the selected by you summarized data entering this command: **hds-query squeeze** <SYSTEM> <HDS ID> <FIELD LIST> <START> <END> <PAGED> <AGGREGATION SIZE> <FUNCTION>.

Table 3.6. Hds-query Command Notation

Notation	Description
SYSTEM	Enter trafip or slaview
HDS ID	
FIELD LIST	Refer on Field list section.
START	Start time in Timestamp format.
END	End time in Timestamp format.
PAGED	1 for paged output 0 otherwise.
AGGREGATION SIZE	Time interval in seconds in which function will be applied.
FUNCTION	Choose the function: sumsq (sum of squares), sum , avg , count , max or min

Field list

Select the list of fields to be used.

Table 3.7. TRAFip - List of Fields

TRAFIP Fields	Syntax
*	All TRAFips fields'
Source packets	pktAb
Destination packets	pktBa
Source flows	flwAb
Destination flows	flwBa
Source bytes	bytAb
Destination bytes	bytBa

Table 3.8. SLAview - List of Fields

SLAview Fields	Syntax
*	All SLAviews fields'
[0-23]	Example: "0,1,2,5-8" , "9,10,11,12-18,22,23"

Command hostname

Use this command to change the appliance hostname.

The syntax is: **hostname** <NAME>.

Table 3.9. Hostname command

Notation	Description
NAME	Hostname. Fill with a string.

Command interface

Use this command to visualize and change interface's configuration.

To visualize interface's configuration, enter **show interface**. Besides, to display more specific information about the interface, like Speed and Supported link modes, for instance, type the command `m_bold(show interface <INTERFACE> link-status)`.

To assign an IPv4 address for an interface, use the command: **interface** <INTERFACE>[:<LABEL>] **ifaddr** <IP>/<MASK>.

To assign an IPv6 address for an interface, use the command: **interface** <INTERFACE>[:<LABEL>] **ifaddr6** <IPV6>/<MASK>.

To remove an IPv4 address from an interface, use the command: **interface** <INTERFACE>[:<LABEL>] **ifaddr remove**.

To remove an IPv6 address from an interface, use the command: **interface <INTERFACE>[:<LABEL>] `ifaddr6 remove`**.

To up an interface, enter **interface <INTERFACE> `up`**.

To down an interface, enter **interface <INTERFACE> `down`**.

To set the protocol as bridge, type: **interface <INTERFACE> `bridge`**.

To change a MAC address, enter **interface <INTERFACE> `hwaddr <MAC>`**.

To clean the network information of all the interfaces, use the command: **interface `reset`**.

Important

Be careful using the last command, because the MAC address' change can invalidate the license of TRAFip.

Table 3.10. Interface Command

Notation	Description
INTERFACE	"netX", where "X" is the interface number
LABEL	An integer positive value. Use it to create additional virtual interfaces for an interface.
MAC	A valid MAC address
IP	A valid IP address
MASK	An IP mask or an integer complementing the CIDR notation

Command logview

Using this command, you can visualize the logs available on the system. To display all of them, enter the command: **logview <SYSTEM> `list`**.

To show a continuous log output, you may use the following command: **logview <SYSTEM> `stream <LOG>`**.

To display the whole log on output, type: **logview <SYSTEM> `all <LOG>`**. While the log is being shown, you may click on **Space key** to see more information.

You can display on output just the last lines of a log, just type: **logview <SYSTEM> `-<N> <LOG> [ZIP_NUMBER]`**.

It's possible to display only the first lines using **logview <SYSTEM> `+<N> <LOG> [ZIP_NUMBER]`**.

Table 3.11. Logview Command

Notation	Description
N	A positive integer, representing the number of lines to be shown.
LOG	The log you want to analyse. You also can enter SQL for SQL server logs or WEB for web server logs.

Notation	Description
ZIP_NUMBER	When a log has more than one file, you may see a specific file by entering its number.
SYSTEM	It can be TRAFIP or BASESYSTEM .

Command ntp

Entering this command, you can view Network Time Protocol (NTP) configuration and manage the ntp servers.

To show NTP configuration, including information about its state, type **show ntp**. The output will be like this:

```
TelcoAppliance> show ntp
NTP configuration:
    server-1: 0.pool.ntp.org
    server-2: 1.pool.ntp.org
    server-3: 0.br.pool.ntp.org
    state: on
```

To enable NTP, just type: **ntp state on**. And to disable NTP, type: **ntp state off**.

To set an NTP server in the list, type **ntp add server<N> <HOST>**

To remove an NTP server from the list, enter the command: **ntp remove server<N>**.

To stop NTP process (**ntpd**), enter: **ntp stop**. To start it, enter: **ntp start**. To restart it, enter: **ntp restart**.

Notation:

Table 3.12. NTP Command Notation

Notation	Description
N	Position of the server in the list, from 1 to 3
HOST	NTP server; may be an IP address or a name

Command ntpquery

NTPQuery is a NTP server monitoring tool. It means you can verify if ntp servers is working well.

The syntax is: **ntpquery <HOST>**. The **HOST** is the NTP server which will receive the queries and it may be an IP address or a host name.

The output will have the following form:

```
remote          refid  st t when poll reach delay  offset jitter
=====
+pcdsh05.on.br  .IRIG. 1  u 537 1024 377  14.724  4.759  1.418
*gps.ntp.br     .GPS.  1  u 254 1024 377   5.264   3.278 135.338
+clock1.redhat.c .CDMA. 1  u  71 1024 377  132.353  4.057  1.041
```

```
-ntp1.ja.net      .GPS.  1  u 111  1024 377  222.560 22.703 23.326
+clock.tl.fukuok .GPS.  1  u  30  1024 377  295.849  3.524  0.112
```

Table 3.13. Ntpquery Command Notation

Column	Description
remote	Server and peer entries listed in the configuration file
refid	Current source of synchronization
st	Stratum
t	Type, where u=unicast, m=multicast, l=local and -='dont know'
when	The time in seconds since the peer was last heard
poll	The poll interval, in seconds
reach	The status of the reachability register
delay	The lastest delay, in milliseconds
offset	The offset, in milliseconds
jitter	The jitter, in milliseconds

The characters beside the remote column represent the synchronization status of each peer.

Table 3.14. Ntpquery - Left margin notation

Character	Meaning
+	candidate - acceptable peer, but not the current system peer
-	outlyer - discarded peer
*	sys.peer - declared system peer

To monitor a NTP server on debugging mode, type: **ntpquery debug <HOST>**.

Tip

To see and configure your NTP servers, use the ntp command

Command packet-dump

Packet-dump is a package analyzer. It means you can capture packets for analysis only using this command.

To only capture packets from a specific interface, you have to use the syntax: **packet-dump interface <netX>**.

To define the number of packets to be captured, use the command: **packet-dump packets <number>**.

To only capture packets from a specific port, you have to use the syntax: **packet-dump port <port>**. You can select more than one port, only you have to do is separate the ports you want with comma. It will be like this: **packet-dump port <port1,port2,...,portN>**.

If you do not want capture packets from a specific port, type the command: **packet-dump notport <port>** or **packet-dump notport <port1,port2,...,portN>**.

To only capture packets from a specific host, you have to use the syntax: **packet-dump host <host>**. You can select more than one host, only you have to do is separate the hosts you want with comma. It will be like this: **packet-dump host <host1,host2,...,hostN>**.

If you do not want capture packets from a specific host, type the command: **packet-dump nohost <host>** or **packet-dump nohost <port1,port2,...,portN>**.

To not resolve IP addresses and ports in the captured packets, use parameter **-n**. So, use the syntax: **packet-dump -n**.

Important

All the previous parameters work together.

Table 3.15. Packet-dump Command Notation

Notation	Description
netX	A valid interface where X is the number of the interface. To view your interfaces, type the command show interface
number	A positive number
port	A valid port number
host	A valid host IP Address

See the following example:

```
TelcoAppliance> packet-dump interface net0 port 22 packets 5
telco-tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on net0, link-type EN10MB (Ethernet), capture size 65535 bytes
11:04:17.670151 IP trafipfed02.telco.ssh > 10.0.0.233.54859: Flags [P.],
  seq 2920521486:2920521630, ack 3564702542, win 201, length 144
11:04:17.671205 IP trafipfed02.telco.ssh > 10.0.0.233.54859: Flags [P.],
  seq 144:272, ack 1, win 201, length 128
11:04:17.671520 IP 10.0.0.233.54859 > trafipfed02.telco.ssh: Flags [.],
  ack 272, win 256, length 0
11:04:17.673179 IP trafipfed02.telco.ssh > 10.0.0.233.54859: Flags [P.],
  seq 272:688, ack 1, win 201, length 416
11:04:17.674161 IP trafipfed02.telco.ssh > 10.0.0.233.54859: Flags [P.],
  seq 688:864, ack 1, win 201, length 176
5 packets captured
9 packets received by filter
0 packets dropped by kernel
```

Command password

To update user authentication, use the command **password**.

Procedure 3.1. Update user authentication steps

1. Enter the command **password**;

2. Type the new password;
3. Retype the new password;
4. Enter the command **apply**;
5. Enter the command **save**

Command patchtool

This feature allows you to apply official patches on the system.

Every patch has the following structure:

- `tmpatch-<build_version>-<sequence_number>.patch`

To install a patch, enter the command: **patchtool install <http|https>://<host>:<port>/<patch_file>**. After this, it's necessary to enter with the command: **patchtool apply <patch sequence>**.

There is a command that will show you the patch description, if it exists. For this purpose, use the command: **patchtool details <patch sequence>**.

To apply all patches installed for this version, use the command: **patchtool apply-all**.

If you want to list all the patches installed, enter: **patchtool list**.

If you want to remove the patches, type: **patchtool erase**.

By default, every system update erases all the patches installed.

Important

You will need to contact the Telcomanager support to get the patches.

Command ping

This command sends ICMP echo messages to test the connection and latency between two network connections.

To send echo messages: **ping [ipv4 | ipv6] <HOST>**

To send echo messages filled with a pattern: **ping [ipv4 | ipv6] <HOST> data <PATTERN>**

To decide the number of times to repeat the ping: **ping [ipv4 | ipv6] <HOST> repeat <COUNT>**

To define a data length to the messages: **ping [ipv4 | ipv6] <HOST> size <SIZE>**

To send echo messages without resolving names: **ping [ipv4 | ipv6] <HOST> no-dns**

Important

When the IP version is not specified, the system consider it as IPv4.

Table 3.16. Ping Command Notation

Notation	Description
HOST	Destination IP address or hostname to ping.

Notation	Description
PATTERN	Hexadecimal (0-9a-fA-F) representation of a bit pattern.
COUNT	Number of packets to send. It is a positive integer and the default is 5 packets.
SIZE	Number of bytes in a packet. It is a positive integer and the default is 56 data bytes.

You may enter all the parameters at once. Look the following example:

```
TelcoAppliance> ping www.google.com.br repeat 3 size 56
PING www.google.com.br (173.194.119.63): 56 data bytes
64 bytes from 173.194.119.63: icmp_seq=0 ttl=55 time=59.194 ms
64 bytes from 173.194.119.63: icmp_seq=1 ttl=55 time=30.682 ms
64 bytes from 173.194.119.63: icmp_seq=2 ttl=55 time=31.127 ms
--- www.google.com.br ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 30.682/40.334/59.194/13.337 ms
```

Command poweroff

This command is used to turning off the system.

You can use **poweroff** to turn off after confirming or **poweroff ASAP** to turn off as soon as possible.

Command probe

You can create probes with the following types: **DNS**, **HTTP**, **TWAMP**, **ICMP**, **SSH** or **TCPCConnect**. The type of probe determines what the probe sends to the server.

To create a DNS probe, enter: **probe create DNS name <NAME> destination <HOST> URL <URL>**.

To create a HTTP probe, enter: **probe create HTTP name <NAME> URL <URL>**.

To create a TWAMP probe, enter: **probe create TWAMP name <NAME> destination <HOST> num_packets <NUMBER> light <yes|no> packet_interval <TIME> payload <BYTES> source <HOST> [port <NUMBER>] [type-p <DSCP>]**.

To create a ICMP probe, enter: **probe create ICMP name <NAME> destination <HOST> num_packets <NUMBER> packet_size <BYTES> packet_interval <TIME> high_latency_discard <NUMBER> low_latency_discard <NUMBER>**. The parameters **high_latency_discard** and **low_latency_discard** have zero as default value and they define how many packets will be discarded from the statistics.

To create a SSH probe, enter: **probe create SSH name <NAME> destination <HOST> port <PORT>**.

To create a TCPCConnect probe, enter: **probe create TCPCConnect name <NAME> destination <HOST> port <PORT>**.

You can edit a probe using its index or its name. To edit it using the index, enter: **probe edit index <ID_VALUE> <PARAM> <NEW_VALUE>**. To edit it using the name, enter: **probe edit name <ID_VALUE> <PARAM> <NEW_VALUE>**.

To set the limit of probe threads, type the following command: **probe tcp_max_threads <NUMBER>**. To view the configured limit, enter: **show probe tcp_max_threads**.

To visualize all probes configuration, enter: **show probe**. If you want to see a specific probe configuration, type the command **show probe index <INDEX>** or the command **show probe name <NAME>**. For instance: show probe 1

To visualize all probes statistics, enter: **show probe stats**. If you want to see a specific probe statistics, enter the previous command with the probe index. For instance: show probe stats 1

To delete a probe by index, type: **probe remove <INDEX>**. To remove a probe by name, type: **probe remove name <NAME>**.

To delete all probes at once, type: **probe remove all**.

After to create or to remove a probe, it is necessary to type the **probe apply** command. Do not forget to save this change using the **probe save** command.

Table 3.17. Probe Command Notation

Notation	Description
NAME	Probe name. Attention: It must be unique!
HOST	A valid IP address
URL	A valid URL
PORT	A valid TCP port
BYTES	The packet size in bytes
TIME	The packet interval in milliseconds
NUMBER	A positive integer
DSCP	A positive integer between 0 and 63
INDEX	When you create a probe, it receives a number. This is the probe index and it is always a positive integer or zero.
ID_VALUE	It can be the probe index or the probe name. Only used in probe edition.
PARAM	Probe param to be edited.

Command process

You can use this command to display the processes that are running or to kill any of them.

To list the processes, type the command **show process**.

Table 3.18. Process Command - Output format

Column	Description
PID	Process ID
%CPU	How much of the CPU is being used
%MEM	How much memory the process is using

Column	Description
VSZ	Virtual Memory Size of the process in KiB
RSS	Resident Set Size in KiB
STAT	Process status
STIME	Process start time
TIME	Total CPU usage
PROCESS	Process name

To kill a process, type **process kill <PID>**.

Command prompt

Entering this command you can modify the string to be displayed on CLI prompt.

To see the current string, type **show prompt**.

To change the CLI string use the following syntax:

prompt <STRING>

<STRING> is the new string to be displayed on CLI prompt and it has the maximum length of 32 characters.

For instance:

```
TelcoAppliance> show prompt
Prompt configuration:
    string: TelcoAppliance
TelcoAppliance> prompt Test
```

Note: Do not forget to **apply** and **save**.

Command restart

Use this command to restart system. You always have to enter it after **update** command.

Command restore

You can restore configuration to start-up conditions or to factory conditions.

In this first option, enter the command: **restore startup**.

In the second one, enter the command: **restore factory**.

Command resum

If you deserve re-summarize the interval between two instants, you have to use this command.

The full syntax of this command is: **resum** <SYSTEM> <YYYY/MM/DD> <HH:mm> <YYYY/MM/DD> <HH:mm>.

Notation:

Table 3.19. Resum Command Notation

Notation	Description
SYSTEM	trafip or slaview
YYYY	4-digit year
MM	2-digit month
DD	2-digit day
HH	2-digit hour
mm	2-digit minute. It will be rounded to a multiple of 5

To check the status of the current re-summarization, enter: **resum** <SYSTEM> **status**.

To stop a re-summarization process, type: **resum** <SYSTEM> **cancel**.

Command route

The **route** command is used to manager the IP routing tables.

To display the current route configuration, enter: **show route**. The output will show the following information: Destination, Netmask, Gateway, Interface and Flags.

Adding route

To bind default route to gateway, enter: **route add [ipv4 | ipv6] default gw <IP>**.

To bind target to a route by gateway, enter: **route add [ipv4 | ipv6] <IP>/<MASK> gw <IP>**.

To bind default route to device, enter: **route add [ipv4 | ipv6] default dev <INTERFACE>**.

To bind target to a route by device, enter: **route add [ipv4 | ipv6] <IP>/<MASK> dev <INTERFACE>**.

Removing route

To unbind default route from gateway, type: **route del [ipv4 | ipv6] default gw <IP>**.

To unbind target from a route by gateway, type: **route del [ipv4 | ipv6] <IP>/<MASK> gw <IP>**.

To unbind default route from device, type: **route del [ipv4 | ipv6] default dev <INTERFACE>**.

To unbind target from a route by device, type: **route del [ipv4 | ipv6] <IP>/<MASK> dev <INTERFACE>**.

Table 3.20. Route Command Notation

Notation	Description
IP	A valid IPv4 or IPv6 address

Notation	Description
MASK	An IP Mask
INTERFACE	"netX", where "X" is the interface number

Important

When the IP version is not specified, the system consider it as IPv4.

Command save

After apply a modification using the command **apply**, you have to type the command **save** if you really want this modification to be saved.

For instance:

```
TelcoAppliance> show prompt
Prompt configuration:
    string: TelcoAppliance
TelcoAppliance> prompt Test
TelcoAppliance> apply
Please, wait.
Setting up phase0
Setting up phase1
Setting up phase2
Setting up phase3
(Unsaved) Test> save
Test>
```

Command service

You will use this command to manage the services. The service's name can be **trafip**, **scheduler**, **web** or **sql**.

To view which service is "ON", enter **show service**.

To turn on or turn off Trafip service, enter **service <ACTION> trafip**. Enter "on" or "off" in <ACTION>.

To stop a service, enter **service stop <SERVICE_NAME>**.

To start a service, enter **service start <SERVICE_NAME>**.

To restart a service, enter **service restart <SERVICE_NAME>**.

Table 3.21. Services

Service	Description
Trafip	Related to Trafip processes
Scheduler	Affect scheduled processes
Web Service	Affect Web access
SQL Service	Related to Database processes

Important

This command does not need to be applied and saved, so be careful!

Command smart-diag

Use **smart-diag** command to consult SMART information from HD.

It's also possible to test this functionality. Choose **short-test** parameter for a faster test or **long-test** parameter to obtain more specific results.

```
TelcoAppliance> smart-diag
TelcoAppliance>
TelcoAppliance>
TelcoAppliance> smart-diag short-test
TelcoAppliance>
TelcoAppliance>
TelcoAppliance> smart-diag long-test
TelcoAppliance>
```

Command show

Using this command, the running system information can be displayed on screen.

This command does not work just by itself, it needs to be completed. So, the full syntax is: **show <OPTION>**

All the possibilities to <OPTION> are shown in the following table:

Table 3.22. Show command

Option	Description
all	View all system configuration.
arptable	Show arp table.
bridge	View bridge configuration.
clock	Displays system clock.
cpu	View CPU statistics.
diag	View interface diagnostics.
disk-cache	Appliance tuning.
dns	View dns configuration.
flowcollect	View the flow collector configuration.
flow-probe	View flow-probe configuration.
flow-sampling	View flow sampling configuration.
hostname	View hostname configuration.
interface	View interface configuration.
memory	View memory usage statistics.

Option	Description
ntp	View NTP configuration.
probe	View probe information or configuration.
process	View process list.
prompt	Display CLI string configuration.
route	View route configuration.
service	View service management utility.
snmp-cfg	View appliance SNMP agent configuration.
speed	View interface speed configuration.
storage	View data storage management utility.
uptime	View uptime.
version	Displays system version.
webserver	View virtual root configuration.

Show all

This option displays all already configured parameters.

Show arptable

To show the arp table (IP address, hardware type, flags, hardware address, mask and device), type: **show arptable**.

Show bridge

Enter this command to view bridge configuration.

Type **show bridge** to view all configured bridges or **show bridge <BRIDGE>** to view a specific one.

Show clock

Something in the following format will be printed on screen displaying the system's time and date:

<WEEKDAY> <MONTH> <DAY> <TIME> <YEAR>

Notation:

Table 3.23. Show Clock Notation

Notation	Description
WEEKDAY	Day of the week
MONTH	Month
DAY	Day
TIME	"HH:MM:SS"; "H" stands for hours, "M" for minutes, "S" for seconds
YEAR	Full year notation

```
TelcoAppliance> show clock
Wed Oct  1 09:37:35 2014
```

Show cpu

It displays CPU statistics on the screen.

```
TelcoAppliance> show cpu
procs -----memor----- -swap- --io-- -system- ----cpu----
 r  b swpd free   buff cache si so  bi bo  in cs  us sy id wa
 1  0  0    1712048 6768 291500 0  0   32 21  202 468  2  1  94 4
```

Show diag

To view interface diagnostics, enter: **show diag interface <INTERFACE>**.

To view interface statistics, enter: **show diag interface <INTERFACE> stat**.

Remember: <INTERFACE> has to be replaced by "netX", where "X" is the interface number.

```
TelcoAppliance> show diag interface net0
      Supported link modes:   10baseT/Half 10baseT/Full
                             100baseT/Half 100baseT/Full
                             1000baseT/Full

      Supports auto-negotiation: Yes

      Advertised link modes:  100baseT/Full
      Advertised pause frame use: No
      Advertised auto-negotiation: Yes

      Speed: 1000Mb/s
      Duplex: Full
      Auto-negotiation: on
      MDI-X:
      Link detected: yes
```

Show disk-cache

It displays the disk-cache configured parameters. To set them, go to disk-cache section.

```
TelcoAppliance> show disk-cache
disk-cache configuration:
  dirty_ratio:    20
  dirty_expire:   3000
  dirty_background_ratio: 10
  highmem_is_dirtyable: 0
```

The 0 ('zero') value in **highmem_is_dirtyable** means that it was set with **no** parameter. When this option is configured with **yes** parameter, the value will be shown is 1 ('one').

Show dns

It displays DNS (Domain Name System) configuration.

```
TelcoAppliance> show dns
DNS configuration:
    primary: 10.0.0.13
    secondary: 10.0.0.2
```

Show flowcollect

It displays the maximum number of templates received by the collector.

```
flowcollect configuration:
    max_templates: 10
```

Show flow-probe

Inserting the **show flow-probe** command, the flow-probe configuration will be printed on screen.

```
TelcoAppliance> show flow-probe
FLOW PROBE configuration

    Status           Enabled
    Destination IP   127.0.0.1
    Destination Port  63636
    Active timeout   90
    Inactive timeout  15
```

Show flow-sampling

The **show flow-sampling** command displays the minimum number of octets to not discard a flow.

To set this value, use the **flow-sampling** command.

Show hostname

It displays the appliance hostname.

```
TelcoAppliance> show hostname
Hostname: repl-114
```

Show interface

To view a specific interface configuration: **show interface [INTERFACE]**.

```
TelcoAppliance> show interface net0
INTERFACE configuration

net0    protocol: bridge
```

You might get more details about the interface configuration typing: **show interface [INTERFACE] link-status**.

```
TelcoAppliance> show interface net0 link-status
Settings for net0:
    Supported link modes:   10baseT/Half 10baseT/Full
                           100baseT/Half 100baseT/Full
                           1000baseT/Full

    Speed: 1000Mb/s
    Duplex: Full
    Auto-negotiation: on
    Link detected: yes
```

Show memory

To show the memory usage statistics, enter **show memory**.

```
TelcoAppliance> show memory ?
show memory - Memory usage statistics

OVERVIEW
  show memory
```

Show ntp

Shows the NTP (Network Time Protocol) configuration.

```
TelcoAppliance> show ntp
NTP configuration:
    server-1: 0.pool.ntp.org
    server-2: 1.south-america.pool.ntp.org
```

```
server-3: 0.br.pool.ntp.org
state: on
```

Show probe

To view probe configuration, enter: **show probe**.

To display probe statistics, enter: **show probe stats**.

Finally, to display the limit of probe threads, enter: **show probe tcp_max_threads**.

Show process

To show all processes, enter: **show process**.

Show prompt

This command prints on screen the CLI string.

```
TelcoAppliance> show prompt
Prompt configuration:
    string: TelcoAppliance
```

Show route

You can view the route configuration entering the command: **show route**.

```
TelcoAppliance> show route
Route configuration:
      Destination      Netmask      Gateway      Flags
      default          10.0.0.1
```

Show service

Displays the status of each service (Trafip, Scheduler, Web Service or SQL service).

```
TelcoAppliance> show service
Service      status
Trafip       ON
Scheduler    ON
Web Service  ON
SQL service  ON
```


Show snmp-cfg

Shows the appliance SNMP agent configuration.

```
TelcoAppliance> show snmp-cfg
snmp-cfg configuration:
  enable
  community:      public
  syslocation:    Unknown
  syscontact:     admin@company
  sysname:        TelcoAppliance
```

Show speed

Enter **show speed** to print on screen the interface speed configuration.

```
TelcoAppliance> show speed
Speed configuration:
interface: net0
  autoneg: on
```

Show storage

It displays the name, the id, the total, free and used size of storage.

```
TelcoAppliance> show storage
```

Name	Id	Size	Used	Free
storage	1	0.0	-----	-----
- Trafip FileSystem	-	28.5G	428.9M	28.1G

Show uptime

Typing you can view the uptime, the number of users and the load average.

Show version

It makes possible to view the model, the serial number (when it's already configured), the factory, UUID1, UUID2, the image, the version and the build.

Show webserver

It displays the vroot used to access the web.

Command show-cfg

This command is used to checking a modification before to apply.

The full syntax is: **show-cfg <OPTION>**

All the possibilities to <OPTION> are shown in the following table:

Table 3.24. Show-cfg command

Option	Description
all	View all temporary system configuration.
bridge	View temporary bridge configuration.
dns	View temporary dns configuration.
flow-probe	View temporary flow-probe configuration.
interface	View temporary interface configuration.
ntp	View temporary NTP configuration.
probe	View temporary probe information or configuration.
prompt	Display temporary CLI string configuration.
route	View temporary route configuration.
snmp-cfg	View temporary appliance SNMP agent configuration.
speed	View temporary interface speed configuration.

For instance:

```
TelcoAppliance> show ntp          #Checking ntp state
NTP configuration:
    server-1: 0.pool.ntp.org
    server-2: 1.pool.ntp.org
    server-3: 0.br.pool.ntp.org
    state: on
```

```
TelcoAppliance> ntp state off    #Changing ntp state
```

```
TelcoAppliance> show ntp          #ntp state before to apply
NTP configuration:
    server-1: 0.pool.ntp.org
    server-2: 1.pool.ntp.org
    server-3: 0.br.pool.ntp.org
    state: on
```

```
TelcoAppliance> show-cfg ntp     #Checking the modification before apply
NTP configuration:
    server-1: 0.pool.ntp.org
    server-2: 1.pool.ntp.org
    server-3: 0.br.pool.ntp.org
    state: off
```

Command show-how

Using this command, you will can replicate running system information in other system due to the fact that the commands are printed exactly like they were configured.

Table 3.25. Show-how command

Option	Description
all	Commands to replicate configuration.
bridge	Commands to replicate bridge configuration.
dns	Commands to replicate DNS configuration.
flow-probe	Commands to replicate flow-probe configuration.
interface	Commands to replicate interface configuration.
ntp	Commands to replicate NTP configuration.
probe	Commands to replicate probe configuration.
prompt	Commands to replicate CLI string configuration.
route	Commands to replicate route configuration.
snmp-cfg	Commands to replicate SNMP agent configutation.
speed	Commands to replicate interface speed configuration.

Look the following example:

```
TelcoAppliance> show-how prompt
prompt TelcoAppliance
```

Command snmp

The **Simple Network Management Protocol (SNMP)** is an application-layer protocol and is used to manage and monitor network elements.

At CLI, the following SNMP commands are available: **snmp get**, **snmp walk**, **snmp bulkget** and **snmp bulkwalk**.

Use **snmp get** to communicate with a network entity using SNMP GET requests. The full syntax is: **snmp get <IP>[:PORT] <COMMUNITY> <VERSION> <OID> [AUTH_TYPE USER PASSWORD_TYPE PASSWORD PRIVACY_PASSWORD]**.

Use **snmp walk** to retrieve a subtree of management values using SNMP GETNEXT requests. The full syntax is: **snmp walk <IP>[:PORT] <COMMUNITY> <VERSION> <OID> [AUTH_TYPE USER PASSWORD_TYPE PASSWORD PRIVACY_PASSWORD]**.

Use **snmp bulkget** to communicate with a network entity using SNMP GETBULK requests. The full syntax is: **snmp bulkget <IP>[:PORT] <COMMUNITY> <VERSION> <OID> [AUTH_TYPE USER PASSWORD_TYPE PASSWORD PRIVACY_PASSWORD]**.

Use **snmp bulkwalk** to retrieve a subtree of management values using SNMP GETBULK requests. The full syntax is: **snmp bulkwalk <IP>[:PORT] <COMMUNITY> <VERSION> <OID> [AUTH_TYPE USER PASSWORD_TYPE PASSWORD PRIVACY_PASSWORD]**.

Important

The last two commands, **snmp bulkwalk** and **snmp bulkget**, utilize the SNMP GETBULK message, which is not available in SNMPv1.

Table 3.26. SNMP Command Notation

Notation	Description
IP	IP address of the device. It can be IPv4 or IPv6.
PORT	SNMP port. When this parameter is not specified, the system consider the default port (161).
COMMUNITY	SNMP community string. Only for SNMPv1 and SNMPv2. Check the Tip below.
VERSION	Specifies the version of SNMP used to send the traps. The versions available here are: "1", "2c" and "3".
OID	ASN.1 object identifier

The table below shows the SNMP version 3 options:

Table 3.27. SNMPv3 parameters

Notation	Description
AUTH_TYPE	The security level. It can be noAuthNoPriv (No Authentication, No Privacy), authNoPriv (Authentication, No Privacy) or authPriv (Authentication, Privacy).
USER	User security name.
PASSWORD_TYPE	Authentication type. It can be MD5 or SHA.
PASSWORD	Authentication passphrase.
PRIVACY_PASSWORD	Password.

Tip

The Default Read-only community string is "public".

Command snmp-cfg

Configure your Appliance SNMP Agent using this command.

First of all, you can visualize the current SNMP Agent's configuration. Just type: **show snmp-cfg**.

See the example below:

```
TelcoAppliance> show snmp-cfg
snmp-cfg configuration:
    enable
```

```
community:    public
syslocation:  Unknown
syscontact:   admin@company
sysname:      TelcoAppliance
```

To enable SNMP configuration, enter: **snmp-cfg enable**. To disable, enter: **snmp-cfg disable**.

To define SNMP community string, enter: **snmp-cfg community <STRING>**. For instance, "public" or "erlang2".

To define location of SNMP device, just enter: **snmp-cfg syslocation <STRING>**.

To set contact's information, type **snmp-cfg syscontact <EMAIL>**.

Finally, to set the name, enter: **snmp-cfg sysname <STRING>**.

Command speed

The speed command is used to configure the speed of an Ethernet interface.

To see your current speed configuration, type: **show speed**. To see a specific interface speed, type: **show speed <INTERFACE>**.

The negotiation mode enables automatic speed configuration. To active this mode, enter **speed <INTERFACE> autoneg on**. To deactivate, enter **speed <INTERFACE> autoneg off**.

You can set the interface speed using the command: **speed <INTERFACE> <RATE>**.

You also can set the interface multiplexing mode and choose between **half** or **full** operation. Just enter the command: **speed <INTERFACE> duplex <MUXING_MODE>**.

Table 3.28. Speed Command Notation

Notation	Description
INTERFACE	"netX", where "X" is the interface number
RATE	data rate (in Mbps); Options: "10", "100" or "1000"
MUXING_MODE	multiplexing mode; Options: "half" or "full"

Command storage

To manage your storage objects, use this command.

To format your storage, enter: **storage format <DEVICE ID> [swap <GB>] [gpt]**

To check the storage, you can use the command: **storage check_fs <DEVICE ID>**. It's important to remember this command needs to be run on the rescue mode, when the filesystem is unmounted. If you try to run this command on a mounted filesystem, it may cause a severe filesystem damage. So, be very careful using this feature.

This command's help shows two more parameters: **storage write_magic <DEVICE ID>** and **storage read_magic <DEVICE ID>**. These commands are used by Telcomanager support team to detect possible problems.

Notation:

Table 3.29. Storage Command Notation

Notation	Description
Device ID	Device id. To discover the id, use the show storage command
GB	The size of swap partition.
gpt	Optional parameter. It is used to format the device using GPT.

Command traceroute

This command prints the route that packets take to a network host.

Full command syntax: `traceroute <HOST>`

Notation:

Table 3.30. Traceroute Command Notation

Notation	Description
HOST	Destination address or hostname

For instance:

```
TelcoAppliance> traceroute www.google.com
traceroute to www.google.com (173.194.119.51), 64 hops max
 1  10.0.0.1 (10.0.0.1) 0.367ms 0.331ms 0.419ms
 2  192.168.1.1 (192.168.1.1) 0.793ms 1.288ms 0.887ms
 3  * * *
 4  200.195.81.229 (200.195.81.229) 138.508ms 55.964ms 24.330ms
 5  200.223.41.83 (200.223.41.83) 60.177ms 30.460ms 36.635ms
 6  200.199.62.155 (200.199.62.155) 32.155ms 200.223.50.186
 (200.223.50.186) 34.317ms 200.199.62.157 (200.199.62.157) 32.058ms
 7  200.199.54.88 (200.199.54.88) 42.472ms 200.199.54.184
 (200.199.54.184) 91.030ms 200.223.254.166 (200.223.254.166) 30.039ms
 8  72.14.217.14 (72.14.217.14) 48.066ms 26.846ms 37.650ms
 9  209.85.254.54 (209.85.254.54) 31.331ms 69.958ms 211.027ms
10  72.14.235.143 (72.14.235.143) 55.777ms 26.741ms 38.355ms
11  64.233.175.85 (64.233.175.85) 54.185ms 33.863ms 28.850ms
12  173.194.119.51 (173.194.119.51) 32.774ms 28.505ms 35.291ms
```

Command ts2date

If you want to convert timestamp to date format, you have to use the command **ts2date**.

Full command syntax: `ts2date <TIMESTAMP>`

The output will be in the following format: Date: <YEAR> <MONTH> <DAY> <HOUR> <MINUTE>

Notation:

Table 3.31. Ts2date Command Notation

Notation	Description
TIMESTAMP	A positive integer
YEAR	Full year notation
MONTH	Month, from 1 to 12
DAY	Day
HOUR	Hour, from 0 to 23
MINUTE	Minute, from 0 to 59

Look at the following example:

```
TelcoAppliance> ts2date 1404394200
Date: 2014 07 03 10 30
```

Command update

The command **update** is used to updating the system version. You will need an update file provided by Telcomanager Support. Please, contact our team to get it.

Full command syntax: update <URI>

Notation:

Table 3.32. Update Command Notation

Notation	Description
URI	Location of update file

Check the example:

```
TelcoAppliance> update http://localhost/telco-lfs64-5.8-20121127-16011
9-p1-r16219.bzImage.full
```

Important

The system should not be powered off during the update process.

Command version

Enter **version history** and get a list of all updates.

This list includes the build version, the date on which it was installed, the system architecture (x32 ou x64) and the checksum (without the header).

Command webservice

Enter **webservice vroot <NAME>** to set a string to use it as virtual root, where <NAME> is the string.

For instance, if you type the command **webservice vroot TRAFip**, the web server will respond requests for <IP>/TRAFip.

To erase the virtual root configuration, type **webservice remove**.

Important

After **apply** and **save**, it will be necessary to enter the **service restart web** command.